

TECHNICAL FEATURES

Certified P series material suitable for pressure vessels

Bayonet door closure systems

Hydraulic door opening and locking mechanism

Precured or Orbitread system automation control

Advanced PLC software able to control time, temperature, pressure, DPC functions (precured) automatically

Manufactured at state-of-the-art manufacturing facilities

Advanced safety features with available certification of 2014/68/ EU CE, ASME, EAC

10 year safety guarantee as part of CE/ASME



**HIGHEST
SAFETY
STANDARDS**


DESCRIPTIONS

	Inner Diameter	Length	Capacity	Heating System	Working Pressure	Max. Working Temperature	Tire Curing
AKR 881E	2300 mm/90"	3900 mm/153"	29,50 R 25 x 4 Tires	Electrical / Indirect Steam	7 Bar/100 psi	120 °C	J Hook
AKR 881	2300 mm/90"	4900 mm/193"	29,50 R 25 x 6 Tires	Electrical / Indirect Steam	7 Bar/100 psi	170 °C	Console
AKR 384	3100 mm/122"	4000 mm/158"	27,00 R 49 x 4 Tires	Direct / Indirect Steam	7 Bar/100 psi	170 °C	Console
AKR 434	3500 mm/138"	5000 mm/197"	36,00 R 51 x 4 Tires	Direct / Indirect Steam	7 Bar/100 psi	170 °C	Console
AKR 389	3900 mm/153"	5500 mm/216"	40,00 R 57 x 4 Tires	Direct / Indirect Steam	7 Bar/100 psi	170 °C	Console
AKR 337	4600 mm/181"	3500 mm/138"	59/80 R63 x 2 Tires	Direct / Indirect Steam	7 Bar/100 psi	170 °C	Console

